

Kepler CMOS Camera

KL4040 FI 65mm

4K x 4K at 23 fps

The KL4040 scientific CMOS camera has the same pixel size and imaging area as the popular KAF-16803 CCD, but with 1/3 the noise and 40% higher quantum efficiency. Kepler cooled sCMOS cameras provide ultra-high sensitivity, ultra-low noise, and high frame rates, all at game-changing price to performance ratio.

Technical Data

Sensor Type	Front Illuminated CMOS
Sensor	GPixel GSense4040
Shutter Type	Rolling; Rolling with Global Reset
Active Pixels	4096 x 4096
Pixel Size (microns)	9 x 9 μm
Imaging Area (Diagonal)	36.8 X 36.8 mm (52 mm)
Full Well Capacity (e-)	70000 electrons
Typical Readout Noise	3.7 e-
Dynamic Range	85.2 dB
Frame Rate (fps)	23 fps (QSFP V2)
Cooling Method¹	Air and Liquid
Max. Cooling (Air)	40°C below ambient
Temperature Stability	0.1°C
Dark Current (typical)	0.08 eps at -10C
Interface	USB 3.0 (Optional QSFP ²)
Data Bit Depth	16 bit ³
Optional Shutter	65mm
Optional Mounts	Medium Format Recommended (6x7)
Subarray Readout	Standard
External Trigger In/Out	Standard
SDK / Software	Kepler SDK / FLI Pilot
Weight	4 lbs (1.8 kg)

¹ Liquid circulation connectors sold separately



² QSFP = Quad Small Form factor Pluggable: high speed fiber optic interface

³ 16-bit data merged from two 12 bit converters



Shown with optional 65mm shutter housing

Absolute Quantum Efficiency



See FLIcamera.com for alternate configurations



MADE IN USA



Finger Lakes Instrumentation
FLIcamera.com
USA 585-624-3760